

148-90025



Article Number: 148-90025

Description: HelaCon Plus Push-In Style Wire Connector, Double Spring, 3-Port, Polycarbonate, Orange, 400/pkg

Base Data	Local Order Number	148-90025
	Type	HECP-3
	Color	Orange (OG)
	Features and benefits	<ul style="list-style-type: none"> <li>• Double Spring Technology for safe, secure and reliable connections</li> <li>• Low Insertion Forces + High Retention Values</li> <li>• Accommodates both solid and stranded wire cores</li> <li>• Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards</li> <li>• Low insertion forces reduces buckling of stranded wire</li> <li>• Able to combine solid and stranded within same housing</li> <li>• Separate test port for fast, easy confirmation of connection</li> <li>• Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time.</li> <li>• Max Current Rating to 24 A</li> <li>• Max Voltage Rating to 600 V (c UL us)</li> </ul>
	Quantity Per	bag
	Product Description	Helacon Plus is a unique push-in wire connector with double spring technology. Double spring design requires less insertion force and delivers superior retention values. Helps alleviate repetitive motion injuries often associated with twist-on style connectors.
	Short Description	HelaCon Plus Push-In Style Wire Connector, Double Spring, 3-Port, Polycarbonate, Orange, 400/pkg
	Product Dimensions	
	Length L (Metric)	19.0mm
	Max Current	24A
	Max Voltage	600V
	Number of Conductors	3
	Width W (Imperial)	0.63"
	Width W (Metric)	15.90mm
	Height H (Imperial)	0.41"
	Height H (Metric)	10.45mm
	Depth D (metric)	19.0mm
	Depth D (imperial)	0.75"

148-90025



Material and Specifications		
	Material	Polycarbonate (PC)
	Material Shortcut	PC
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-22°F to +221°F (-30°C to +105°C)
	ROHS Compliant	Yes
	Certification/Specification	ENEC
	UL Listed (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	400
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	7413009000
	Weight (imperial)	3.4lbs