

| _ | | | | | | |
|---|---------|-----|------------------------|------|------|-----|
| | Date | SYM | REVISION RECORD | AUTH | DR. | CK. |
| | 6/24/06 | Α | ADDED "ROHS COMPLIANT" | T.B. | B.S. | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

NOTES:

MATERIAL:

INSULATOR: PVC, RED

CLIP: 302 STN. STL., SPRING TEMPER, NICKEL

PLTD.

SPRING:

RIVET: BRASS, NICKEL PLATED

ROHS COMPLIANT

| Tolerance | Mem | Memory Protection Devices, Inc | | | | |
|-------------------|------------------------|--|-------|------------------|--|--|
| (Except as noted) | 200 | 200 Broad Hollow Road, Farmingdale, New York 11735 | | | | |
| decimal | | | Scale | Drawn By B.S. | | |
| ±.5 (.020) | | | | Approved By T.B. | | |
| Fractional | Title DATE DATE DATE | | | | | |
| ± .8 (.030) | INSULATED BATTERY CLIP | | | | | |
| Angular | Date Drawing N | | umber | | | |
| ± 3° | 6/24/06 ZB3010-A | | | | | |