

	1	2	3	4	5	6	7											
A	IEEE1394 4M PLASTIC:BLACK P1 L ± 50mm IEEE 1394 6M PLASTIC:BLACK P2							A										
B								B										
C	NOTE: 1. CABLE: [28AWG(7/0.127)T.C*1PAIR+AL/MYLAR+SPIRAL(66/0.08)]*2+FILLER+MYLAR*2+BRAID(95%)+PVC JACKET COLOR:MATT BLACK. OD:6.0±0.15mm UL20276 IEEE 1394 CABLE 2.CONNECTOR: P1: IEEE1394 4PIN MALE GOLD PLATED 15u" CONTACT NICKEL PLATED SHELL. P2: IEEE1394 6PIN MALE GOLD PLATED 15u" CONTACT NICKEL PLATED SHELL. 3.HOOD: P1: MOLDED TYPE,COLOR:MATT BLACK. P2: MOLDED TYPE,COLOR:MATT BLACK. 4.TEST REQUEST: <1>.100% OPEN SHORT MIS WIRE TEST <2>.CONTACT RESISTANCE 3 OHMs MAX <3>.INSULATION RESISTANCE 20M OHMs MIN 5.PACKING: SEE P-0039 REV.C PACKING DRAWING PACKING TYPE: DB VP2 (HANKING SIZE MUST BE SMALLER THAN PACKING) PIN OUT P1 GREEN 1 RED 2 BLUE 3 ORANGE 4 SHELL P2 5 6 3 4 2 SHELL EAN Code: 4016032078081 <table><tr><td>ASSMANN WSW P/N</td><td>LENGTH</td></tr><tr><td>AK-1394-104</td><td>1.0 M</td></tr><tr><td>AK-1394-184</td><td>1.8 M</td></tr><tr><td>AK-1394-304</td><td>3.0 M</td></tr><tr><td>AK-1394-504</td><td>5.0 M</td></tr></table>							ASSMANN WSW P/N	LENGTH	AK-1394-104	1.0 M	AK-1394-184	1.8 M	AK-1394-304	3.0 M	AK-1394-504	5.0 M	C
ASSMANN WSW P/N	LENGTH																	
AK-1394-104	1.0 M																	
AK-1394-184	1.8 M																	
AK-1394-304	3.0 M																	
AK-1394-504	5.0 M																	
D								D										
E								E										
F								F										
G	Scale FREE TOLERANCE X. ±X X.X ±X X.XX ±X DIM TOL X.° ±X° X.X° ±X° Angle TOL ① Drawn 06.07.2009 Rale Id. Modification Date Name ASSMANN components Customer-No. ASSMANN WSW-No. AK-1394-104 AK-1394-184 AK-1394-304 AK-1394-504 Drawing-No. ASS 3646 CA rev01 Replace Sheet							G										
H	RoHS compliant							H										
	1	2	3	4	5	6	7											

RoHS compliant



Customer-No.	
ASSMANN WSW-No. AK-1394-104 AK-1394-184 AK-1394-304 AK-1394-504	
Drawing-No.	ASS 3646 CA rev01
Replace	Sheet