### **TDS # CS25**

# **CHEMTRONICS Technical Data Sheet**

## Chemswab™ Presaturated Swab

#### PRODUCT DESCRIPTION

Chemswab<sup>TM</sup> Presaturated Swabs are general purpose, lint-free cleaning swabs. They are excellent for general purpose cleaning of computers, office and laboratory equipment. These highly effective cleaning swabs are for sensitive ideal cleaning surfaces. electronics components, touch keypads, and instrument keyboards, housings. Chemswab<sup>TM</sup> quickly and safely removes handling soils, dirt and oxides from PCB's, mechanical / electrical assemblies and other equipment. Chemswab<sup>TM</sup> electronic especially effective in removing ink and permanent marker.

Chemswab™ Presaturated Swabs contain ultra-pure isopropyl alcohol (91% IPA / 9% Pure Water) on a urethane foam swab.

- Plastic Safe
- Dries Fast
- Leaves No Residue
- Nonabrasive
- Upper Ozone Safe; CFC/HCFC Free

#### TYPICAL APPLICATIONS

Chemswab<sup>TM</sup> cleans and degreases:

- Keyboards and Touch pads
- Cables
- Cabinets and Housings

# TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

<b>Specific Gravity</b>	0.81
Solubility in Wate	er Soluble
Evaporation Rate (Ether = 1)	<1
Appearance	Clear, Colorless Liquid
Flash Point (TCC	) 61° F
Percent Volatile	100%
Shelf life	2 years

#### **COMPATIBILITY**

Chemswab<sup>TM</sup> Presaturated Swabs are generally compatible with most plastics, glass and metals. Compatibility must be checked with all antiglare coatings. As with any chemical product, component compatibility must be determined on a non-critical area prior to use.

<u>Material</u>	Compatibility
Aluminum	Excellent
Buna-N	Good
CPVC	Excellent
Epoxy	Excellent
Neoprene	Good
Noryl <sup>®</sup>	Excellent
Phenolic	Excellent
Cross-Linked PE	Good
Polycarbonate	Poor
Polypropylene	Good
Polystyrene	Poor
PVC	Fair
Teflon <sup>TM</sup>	Excellent
$Tygon^{TM}$	Good
Viton <sup>TM</sup>	Excellent

#### **USAGE INSTRUCTIONS**

Read MSDS carefully prior to use.

### **Chemswab**<sup>TM</sup> **Presaturated Swabs:**

Remove wipe from packet and lightly wipe away any dust or contaminants from surfaces. Allow surface to dry completely before use.

#### **AVAILABILITY**

CS25 25 Premoistened Swabs individually packaged

# TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. Call toll free at: 1-800-TECH-401 (1-800-832-4401).

#### ENVIRONMENTAL IMPACT DATA

ENVIRONMENTAL IMPACT DATA							
CFC	0.0%	VOC	91%				
HCFC	0.0%	HFC	0.0%				
CL Solv.	0.0%	ODP	0.0				

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. The ODP of this product is zero.

#### NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly.

CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

CHEMTRONICS 8125 COBB CENTER DRIVE KENNESAW, GA 30152

1-770-424-4888 REV. A (08/13)

Chemtronics® is a registered trademark of Chemtronics. All rights reserved. Chemswab™ is a trademark of Chemtronics. All rights reserved.

DISTRIB	UTED BY:		