

Article Number: 598-00335

Description: Wire Marker Tape #1, .25" x 1.25", #5, White, 1/pkg

HellermannTyton

Base Data		
	Local Order Number	WMT5
	Туре	WMT
	Color	White (WH)
	Features and Benefits	 Dispenser protects unused markers until needed. Each marker is pre-cut for easy dispense and removal. Markers are coated to protect the printed text from chemicals and abrasion. Dispenser is refillable making it a cost effective and efficient marking system.
	Quantity Per	box
	Product Description	The Wire Marker Tape dispenser is a plastic label dispensing container that provides a convenient, economical system for wire marking. HellermannTyton's wire marker tape features sharp, crisp, pre-printed legends where are coated to resist smearing and abrasion. Each marker is provided on a carrier strip that prevents adhesive contamination prior to installation, assuring permanent, non-flagging marker ends.
	Short Description	Wire Marker Tape #1, .25" x 1.25", #5, White, 1/pkg
Product Dimensions		
	Length L (Imperial)	1.25"
	Length L (Metric)	31.75mm
	Cable Diameter Min. (Metric)	0.00mm
	Width W (Imperial)	0.25"
	Width W (Metric)	6.35mm
	Height H (Imperial)	1.25"
	Height H (Metric)	31.75mm
	Bundle Diameter Min. (Imperial)	0.1"
	Bundle Diameter Min. (Metric)	2.54mm
	Bundle Diameter Max. (Imperial)	0.375"
	Bundle Diameter Max. (Metric)	9.52mm
	Outside Diameter Min. (Imperial)	0.1"
	Outside Diameter Min. (Metric)	2.54mm

generated on: 4/28/2017

598-00335



Product Dimensions	Outside Diameter Max. (Imperial)	0.375"
	Outside Diameter Max. (Metric)	9.52mm
Material and Specifications		
	Material	Tyvek
	Material Shortcut	Tyvek
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +248°F (-40°C to +120°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	3919102055

generated on: 4/28/2017